



NEW: SWISS PRODUCTION

Let's go liquid!

ALSAN 970 F, 971 F, 972 F and Vaporex Seal: now produced in Switzerland

ALSAN 970 F/971 F/972 F are now produced just in time in Weinfelden (Switzerland) according to our own optimized formulation - of course according to high Swiss quality standards. Highest efficiency and performance are guaranteed.



ALSAN 970 F - Art. no 158991

Flexible, pigmented PMMA resin for sealing of all smooth or sprinkled ALSAN PMMA systems.

- ✓ Colored sealing and wear layer
- ✓ Highly abrasion resistant
- ✓ Durably weather resistant
- ✓ UV-, hydrolysis-, alkali-resistant
- ✓ Free from solvent
- ✓ All RAL and NCS colors possible

Consumption:

For smooth surfaces at least 0.6 kg/m²
 For scattered surfaces (quartz sand 04-0.8 mm) approx. 0.8 kg/m²
 The consumption of the sealer can be greatly increased if the scattering grain is different.



ALSAN 971 F - Art. no 235015

Flexibilized PMMA resin for the execution of a structural coating that serves as a repair, bedding and/or coating compound.

- ✓ Coating and repair of mastic asphalt or suitable rolled asphalt
- ✓ Color design or marking of slated bituminous sheeting
- ✓ By adding various sprinkling materials such as Mandurax, natural quartz, Durop, Basalt and grit create non-slip surfaces with a good grip
- ✓ Can also be used on cementitious substrates with appropriate primer
- ✓ All RAL and NCS colors possible

Consumption:

1.0 kg/m² to 1.5 kg/m²
 Depending on the condition of the substrate, a higher consumption may be necessary



ALSAN 970 F, 971 F, 972 F and Vaporex Seal: new produced in Switzerland

Liquid
NEWS



ALSAN 972 F - Art. no 235016

Flexibilized, pigmented PMMA resin for the execution of a structural coating with granules mixed in.

- ✓ Creation of non-slip surfaces without scattering
- ✓ Textured surface for all high-traffic areas in parking garages, on roads or forecourts.
- ✓ No sprinkling of quartz sand or similar necessary.
- ✓ UV-, hydrolysis-, alkali-resistant
- ✓ Extremely abrasion resistant (bauxite as filler)
- ✓ Very high skid resistance, R12 V10 possible
- ✓ Permanently weather resistant
- ✓ No sprinkling or sealing necessary
- ✓ All RAL and NCS colors possible

Consumption:

For flat, smooth surfaces approx. 3.5 kg/m²

ALSAN Vaporex mats are now also produced in Weinfelden. Thanks to optimizations, the production costs could be reduced and the conditions accordingly made more attractive.



ALSAN VAPOREX SEAL - Art. no 111259

Ready-to-install structural mat based on PMMA. It consists of a geometric structure on the bottom side, the top side forms the sealing layer at the same time.

- ✓ Vapor relief and sealing membrane for subsequent Alsan PMMA coating systems
- ✓ Can be laid on damp cementitious surfaces
- ✓ No demolition of the existing coating necessary
- ✓ Short blocking times during refurbishment
- ✓ Considered a full waterproofing system - 2 mm layer thickness

Dimensions / Weight:

2m (L) x 1m (B) x 5mm (H) / 5 kg/m²

Orders: as usual per Intercompany via dossier 503 Prenotec.

For **technical inquiries** Rudolf Schibli (rschibli@alsan.com) and

Rico Wolf (rwolf@soprema.ch) are at your disposal.